

Specialty No. **F3**DRAIN CLOG REMOVER

Type: Drain Cleaners and clog removers from pipes

Application Areas: Degrades organic matter, eliminates fowl odors, Inhibits pathogens, removes Clogs in all types of waste plumbing pipes, Cat litter pans, Garbage, Grease Traps, Municipal waste water, Outdoor privies and vaults, RV & boat holding tanks, Septic pits, tanks, Sewage ejector sumps







Composition: Bio-Doze[™] F3 is a blend of, beneficial, non pathogenic, naturally occurring, non GM bacteria, enzymes, organic acids and Natural Minerals. Bio-Doze[™] F3 can degrade the protein, grease, oil, paper, lignin, cellulose, carbohydrates and other organic waste into basic harmless components.

Bio-Doze™ F3 contains a consortium of bacteria like Bacillus subtilis, B. polymyxa, Aspergillus spp., and a blend of Enzymes like Protease, Lipase, Hemicellulase, Laccase along with organic acids and useful natural minerals. The bacterial composition is as follows:

Bacteria count: 0.5 Billion CFU/gram total viable count.

Aspergillus Spp. 0.05 Billion CFU/gram B. polymyxa 0.05 Billion CFU/gram

Bacillus subtilis 0.25 Billion CFU/gram and other useful bacteria.

Features & Benefits : Bio-Doze™ F3 uses bio-electrochemical remediation process. Free Flowing Powder works on the pH Range: 5.5 to 8.5

Method of Application & Dosage: 100 g Bio-Doze™ F3 per 1 inch dia of the drain pipe is recommended. Allow to work for 15 minutes. For tough problems, allow reaction for 30 minutes and flush with hot water. Repeat steps if necessary.

Limitations: Do not apply under low pH conditions.

Packing: In the unit sizes of 1 Kg, 5 Kg and 25 Kg

Shelf Life & Storage: Shelf life is 9 months from the date of manufacturing in unopened condition. Store in a cool & dry place.

Health & Safety Precautions: No known skin effects. Do not take internally. Use with adequate ventilation